

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: WALL PATCH & REPAIR KIT
PRODUCT CODE: 2030

HMIS CODES: H F R P
0 0 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Custom Building Products, Inc.
ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201
EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846
DATE REVISED : 12-13-99 NAME OF PREPARER : S. TAYLOR

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

COMPONENTS	CAS NUMBER	OCCUPATION EXPOSURE LIMITS		VAPOR PRESSURE		Wt. %
		OSHA PEL	ACGIH TLV	mm Hg @	TEMP	
REPORTABLE						NONE

* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 0.5
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
SOLUBILITY IN WATER: DILUTABLE
APPEARANCE AND ODOR: WHITE MASTIC; SLIGHT AMMONICAL ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A UPPER: N/A

VOC= 0 g/l

EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIREFIGHTING PROCEDURES
NONE

UNUSUAL FIRE AND EXPLOSION HAZARDS
MATERIAL CAN SPLATTER ABOVE 100 DEG.C/212F. DRIED POLYMER FILM CAN BURN.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

NONE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

NONE

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA, AND IRRITATION OF NOSE, THROAT, AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SLIGHTLY IRRITATING TO EYES.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NONE

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: N/A

CHRONIC: N/A

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: FLUSH EYES WITH A LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES.

SKIN CONTACT: FLUSH SKIN WITH LARGE AMOUNTS OF WATER

INHALATION: MOVE SUBJECT TO FRESH AIR

=====
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
CONTAIN SPILL WITH INERT MATERIALS (e.g.SAND, EARTH). KEEP SPILLS AND RUN OFF
OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

WASTE DISPOSAL METHOD
DISPOSE OF SPILLED PRODUCT ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
NONE

OTHER PRECAUTIONS
NONE

=====
SECTION VIII - CONTROL MEASURES
=====

RESPIRATORY PROTECTION
NONE REQUIRED.

VENTILATION
LOCAL EXHAUST.

PROTECTIVE GLOVES
LATEX GLOVES.

EYE PROTECTION
SAFTEY GLASSES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
NONE REQUIRED.

WORK/HYGIENIC PRACTICES
KEEP SPILLED MATERIALS CLEANED UP.

=====
SECTION IX - DISCLAIMER
=====

DISCLAIMER
THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO
BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO
CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND
SUITABLE TO THEIR CIRCUMSTANCES.