

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: TILE LAB OneStep Cleaner & Resealer HMIS CODES: H F R P  
PRODUCT CODE: 3061 1 0 0 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Custom Building Products, Inc.  
ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201  
EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846  
DATE REVISED : 01-16-04 NAME OF PREPARER : STEVE TAYLOR

SECTION II - INGREDIENTS/SARA III INFORMATION

COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE		Wt. %	
		OSHA PEL	ACGIH TLV	mm Hg @	TEMP		
Water	7732-18-5					90-98	
Surfactant	N/A					<2	
Limonene	138-86-3					<1	

\* Chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: APPROX. 212F SPECIFIC GRAVITY (H2O=1): 1.0  
VAPOR DENSITY: 5.14 (DPM) (AIR =1) EVAPORATION RATE (H2O=1): 1.0  
SOLUBILITY IN WATER: COMPLETELY  
APPEARANCE AND ODOR: CLEAR LIQUID, MILD CITRUS ODOR.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A  
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/E UPPER: N/E  
EXTINGUISHING MEDIA: N/A

SPECIAL FIREFIGHTING PROCEDURES  
N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS  
NONE.

=====  
SECTION V - REACTIVITY DATA  
=====

STABILITY: STABLE

CONDITIONS TO AVOID:  
NONE

INCOMPATIBILITY (MATERIALS TO AVOID)  
STRONG OXIDIZERS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS  
CARBON MONOXIDE, CARBON DIOXIDE UPON THERMAL DECOMPOSITION.

HAZARDOUS POLYMERIZATION: MAY NOT OCCUR.

=====  
SECTION VI - HEALTH HAZARD DATA  
=====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION: EXCESSIVE INHALATION MAY CAUSE DROWZINESS, LIGHT HEADEDNESS,  
WEAKNESS, HEADACHE.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN CONTACT SKIN IRRITATION SEEN AS SLIGHT REDNESS.

EYE CONTACT: EYE IRRITATION SEEN AS REDNESS, TEARING.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

REPEATED SKIN EXPOSURE MAY CAUSE IRRITATION.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

N/A

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: DIRECT EYE CONTACT MAY CAUSE IRRITATION. EXCESSIVE INHALATION MAY  
CAUSE NASAL AND RESPIRATORY IRRITATION. PROLONGED OR REPEATED SKIN CONTACT  
MAY CAUSE IRRITATION. INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO  
NOT LISTED AS A CARCINOGEN.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: IMMEDIATELY FLUSH WITH WATER FOR 15 MIN. LIFTING UPPER AND LOWER  
LIDS OCCASIONALLY.

SKIN CONTACT: WASH WITH MILD SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND  
LAUNDER BEFORE REUSE.

INGESTION: IF CONSCIOUS, DILUTE BY GIVING 2 GLASSES OF WATER. KEEP WARM,  
QUIET. GET IMMEDIATE MEDICAL ATTENTION.

INHALED: IF AFFECTED, REMOVE TO FRESH AIR.

=====  
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE  
=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

REMOVE ALL SOURCES OF IGNITION. VENTILATE THE AREA WELL. ABSORB ALL SOLIDS AND SHOVEL INTO CONTAINERS.

WASTE DISPOSAL METHOD

DISPOSE ACCORDING TO FEDERAL, STATE AND LOCAL LAWS AND 40 CFR.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BETWEEN 40 AND 100F.

=====  
SECTION VIII - CONTROL MEASURES  
=====

RESPIRATORY PROTECTION

NONE

VENTILATION

PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

PROTECTIVE GLOVES

IMPERVIOUS SUCH AS RUBBER FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION

SAFETY GLASSES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

NONE.

WORK/PRACTICES

AVOID BREATHING SPRAY MIST.

=====  
SECTION IX - DISCLAIMER  
=====

DISCLAIMER

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.