

MATERIAL SAFETY DATA SHEET

LEVELQUICK DP (DEEP POUR)

HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	E

1. Product And Company Identification

Supplier
CUSTOM BUILDING PRODUCTS
13001 SEAL BEACH BLVD.
SEAL BEACH, CA 90740 UNITED STATES

Company Contact: GEORGE MARCINA
Telephone Number: (323) 582-0846

Manufacturer
CUSTOM BUILDING PRODUCTS
13001 SEAL BEACH BLVD.
SEAL BEACH, CA 90740 UNITED STATES

Company Contact: GEORGE MARCINA
Telephone Number: (323) 582-0846

Supplier Emergency Contacts & Phone Number
GEORGE MARCINA: (323) 582-0846

Manufacturer Emergency Contacts & Phone Number
GEORGE MARCINA: (323) 582-0846

Issue Date: 02/02/2004

Product Name: LEVELQUICK DP (DEEP POUR)

CAS Number: Not Established

MSDS Number: 261

Product Code: 6070

Product Identification Text

THIS MSDS IS APPLICABLE TO THE FOLLOWING PRODUCT:

LEVELQUICK DP (DEEP POUR)

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
CALCIUM ALUMINATE CEMENT	65997-16-2	5 - 20
CALCIUM SULFATE	10101-44-4	5 - 20
LIMESTONE	1317-65-3	0 - 20
PORTLAND CEMENT	65997-15-1	20 - 50
SILICA, CRYSTALLINE	14808-60-7	30 - 60

3. Hazards Identification

Primary Routes(s) Of Entry

EYES, SKIN AND NOSE.

Eye Hazards

CEMENT AND SILICA DUST CAN IRRITATE THE EYES.

Skin Hazards

WET CEMENT, ESPECIALLY AS AN INGREDIENT IN PLASTIC (UNHARDENED) CONCRETE, CAN DRY THE SKIN AND CAUSE ALKALI BURNS.

MATERIAL SAFETY DATA SHEET

LEVELQUICK DP (DEEP POUR)

3. Hazards Identification - Continued

Ingestion Hazards

CEMENT IS HIGHLY ALKALI AND INGESTION MAY DAMAGE DIGESTIVE ORGANS

Inhalation Hazards

PROLONGED EXPOSURE TO CEMENT AND CRYSTALLINE SILICA DUST ABOVE THE THRESHOLD LIMIT VALUE MAY CAUSE SHORTNESS OF BREATH AND SCARRING OF THE LUNGS. DUST MAY ALSO CAUSE IRRITATION OF EYES AND NOSE.

Conditions Aggravated By Exposure

HYPERSENSITIVE INDIVIDUALS MAY DEVELOP SKIN RASH.

THIS PRODUCT CONTAINS ONE OR MORE CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. THE STATE OF CALIFORNIA (PROP. 65) REQUIRES THE ABOVE WARNING IN THE ABSENCE OF DEFINITIVE TESTING TO PROVE THAT THE DEFINED RISKS DO NOT EXIST. WE BELIEVE THIS PRODUCT COMPLIES WITH ALL OTHER APPLICABLE STATE, FEDERAL LAWS AND REGULATIONS GOVERNING MANUFACTURE, DISTRIBUTION AND INTENDED USE.

4. First Aid Measures

Eye

IRRIGATE EYES WITH WATER FOR A MINIMUM OF 15 MIN, RETRACTING EYELIDS; CONSULT A PHYSICIAN IMMEDIATELY.

Skin

WASH EXPOSED AREA WITH SOAP AND WATER IMMEDIATELY. IF RASH DEVELOPS, SEEK MEDICAL ATTENTION.

Ingestion

DO NOT INDUCE VOMITING. IF VICTIM IS CONSCIOUS, GIVE LARGE QUANTITIES OF WATER OR MILK. CONSULT PHYSICIAN.

Inhalation

IF TLV IS EXCEEDED, WEAR APPROPRIATE RESPIRATOR. IMMEDIATELY REMOVE TO FRESH AIR. CONSULT A PHYSICIAN.

5. Fire Fighting Measures

Flash Point: N/A °F

Flash Point Method: N/A

Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

Fire And Explosion Hazards

NONE REQUIRED.

Extinguishing Media

NON-FLAMMABLE.

Fire Fighting Instructions

NONE REQUIRED.

6. Accidental Release Measures

IN CASE MATERIAL IS RELEASED OR SPILLED, CLEAN UP USING DRY METHODS THAT DO NOT CREATE DUST. AVOID BREATHING THE DUST. EMERGENCY PROCEDURES ARE NOT REQUIRED.

MATERIAL SAFETY DATA SHEET

LEVELQUICK DP (DEEP POUR)

7. Handling And Storage

Handling And Storage Precautions

USE DUSTLESS OR WET SYSTEMS WHEN HANDLING AND CLEAN-UP SO THAT EXPOSURE DOES NOT EXCEED TLV.

Work/Hygienic Practices

GOOD HOUSEKEEPING PROCEDURES SHOULD BE FOLLOWED AT ALL TIMES.

8. Exposure Controls/Personal Protection

Eye/Face Protection

SAFETY GLASSES.

Skin Protection

IMPERVIOUS GLOVES SHOULD BE WORN TO PREVENT SKIN CONTACT.

Respiratory Protection

APPROVED NIOSH PARTICULATE FILTER RESPIRATOR.

Other/General Protection

USE MECHANICAL VENTILATION TO KEEP DUST EXPOSURE BELOW TLV RANGES.

Ingredient(s) - Exposure Limits

CALCIUM ALUMINATE CEMENT

OSHA/PEL=15 mg/m³

ACGIH/TLV=10 mg/m³

CALCIUM SULFATE

OSHA/PEL = 5 mg/m³ (RESPIRABLE)

ACGIH/TLV = 10 mg/m³

VAPOR PRESSURE = N/A

PORTLAND CEMENT

OSHA/PEL = 5 mg/m³ (RESPIRABLE)

ACGIH/TLV = 10 mg/m³

VAPOR PRESSURE = N/A

SILICA, CRYSTALLINE

OSHA/PEL = 0.1 mg/m³ (RESPIRABLE)

ACGIH/TLV = 0.05 mg/m³

VAPOR PRESSURE = N/A

THE USE OF BARRIER CREAMS OR GLOVES, IMPERVIOUS BOOTS AND CLOTHING TO PROTECT THE SKIN FROM CONTACT WITH WET CEMENT.

9. Physical And Chemical Properties

Appearance

GRAY OR WHITE POWDER

Odor

ODORLESS.

Chemical Type: Mixture

Physical State: Solid

Boiling Point: N/A °F

Specific Gravity: 2.7

Vapor Density: N/A

Solubility: SLIGHT

Evaporation Rate: N/A

MATERIAL SAFETY DATA SHEET

LEVELQUICK DP (DEEP POUR)

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR.

Conditions To Avoid (Stability)

NONE.

Incompatible Materials

STRONG ACIDS.

Hazardous Decomposition Products

REACTION WITH STRONG ACIDS WILL RELEASE CARBON DIOXIDE.

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations

DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

14. Transport Information

DOT Shipping Label

NOT REGULATED

15. Regulatory Information

U.S. Regulatory Information

THIS PRODUCT IS IN COMPLIANCE WITH THE TOXIC SUBSTANCES CONTROL ACT'S INVENTORY REQUIREMENTS.

16. Other Information

HMIS Rating

Health: 1

Fire: 0

Reactivity: 0

Personal Protection: E

Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA

MSDS Preparer Phone Number: (323) 582-0846

This MSDS Supercedes A Previous MSDS Dated: 12/14/2003

Disclaimer

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

CUSTOM BUILDING PRODUCTS