

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: STUCCO PATCH  
 PRODUCT CODE: 8039

HMIS CODES: H F R P  
 1 0 0 I

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Custom Building Products, Inc.  
 ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201  
 EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846  
 DATE REVISED : 10-06-97 NAME OF PREPARER : STEVE TAYLOR  
 REASON REVISED : SECTION VI, CARCINOGENICITY.

===== SECTION II - INGREDIENTS/SARA III INFORMATION =====

COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE		VAPOR	Wt.
		OSHA PEL	ACGIH TLV	mm Hg @ TEMP	%
SILICON DIOXIDE; SILICA, CRYSTALLINE	14808-60-7	10mg/M3	.3mg/M3	N/A	50
CALCIUM SALTS/ PORTLAND CEMENT			5MG/M3DUST	N/A	35
CALCIUM CARBONATE/ LIMESTONE	1317-65-3		10 mg/M3	N/A	15

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 2.8  
 VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
 SOLUBILITY IN WATER: SLIGHT  
 APPEARANCE AND ODOR: COLORED POWDER NO ODOR

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A  
 FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A UPPER: N/A  
 EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIREFIGHTING PROCEDURES  
NONE REQUIRED.

UNUSUAL FIRE AND EXPLOSION HAZARDS  
NONE REQUIRED.

=====  
SECTION V - REACTIVITY DATA  
=====

STABILITY: STABLE

CONDITIONS TO AVOID  
NONEINCOMPATIBILITY (MATERIALS TO AVOID)  
NONEHAZARDOUS DECOMPOSITION OR BYPRODUCTS  
NONEHAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
HAZARDOUS POLYMERIZATION CANNOT OCCUR.=====  
SECTION VI - HEALTH HAZARD DATA  
=====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

CHRONIC: CEMENT DUST CAN CAUSE INFLAMMATION OF THE LINING TISSUE OF THE INTERIOR OF THE NOSE AND INFLAMMATION OF THE EYE. HYPERSENSITIVE INDIVIDUALS MAY DEVELOP AN ALLERGIC DERMATITUS (skin rash).

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

ACUTE: WET CEMENT, ESPECIALLY AS AN INGREDIENT IN PLASTIC (unhardened) CONCRETE, CAN DRY THE SKIN AND CAUSE ALKALI BURNS. CEMENT DUST CAN IRRITATE THE EYES AND UPPER RESPIRATORY SYSTEM.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
NONEINGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
NONE

HEALTH HAZARDS (ACUTE AND CHRONIC)

THIS PRODUCT CONTAINS ONE OR MORE CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. THE STATE OF CALIFORNIA (PROP. 65) REQUIRES THE ABOVE WARNING IN THE ABSENCE OF DEFINITIVE TESTING TO PROVE THAT THE DEFINED RISKS DO NOT EXIST. WE BELIEVE THIS PRODUCT COMPLIES WITH ALL OTHER APPLICABLE STATE AND FEDERAL LAWS AND REGULATIONS GOVERNING MANUFACTURE, DISTRIBUTION AND INTENDED USE.

CARCINOGENICITY: NTP? YES IARC MONOGRAPHS? YES OSHA REGULATED? YES  
THERE IS SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY OF CRYSTALLINE SILICA

TO EXPERIMENTAL ANIMALS AND HUMANS.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE  
HYPERSENSITIVE INDIVIDUALS MAY DEVELOP SKIN RASH.

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: IRRIGATE EYES WITH WATER; CONSULT PHYSICIAN IMMEDIATELY.

SKIN CONTACT: WASH EXPOSED AREAS WITH SOAP AND WATER IMMEDIATELY.

INHALED: WEAR APPROVED RESPIRATOR IN DUSTY ENVIRONMENT.

=====  
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE  
=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  
CLEAN-UP USING DRY METHODS THAT DO NOT DISPERSE DUST INTO THE AIR.  
AVOID BREATHING THE DUST. EMERGENCY PROCEDURES ARE NOT REQUIRED.

WASTE DISPOSAL METHOD  
CAN BE TREATED AS A COMMON WASTE OR RETURNED TO THE CONTAINER FOR LATTER USE  
IF IT IS NOT CONTAMINATED.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING  
NONE

OTHER PRECAUTIONS  
NONE

=====  
SECTION VIII - CONTROL MEASURES  
=====

RESPIRATORY PROTECTION  
APPROVED NIOSH RESPIRATOR.

VENTILATION  
AVOID GENERATING DUST.

PROTECTIVE GLOVES  
IMPERVIOUS GLOVES SHOULD BE WORN TO PREVENT SKIN CONTACT.

EYE PROTECTION  
THE USE OF TIGHT GOGGLES ARE RECOMMENDED TO PREVENT EYE IRRITATION FROM  
CEMENT DUST.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT  
THE USE OF BARRIER CREAMS OR GLOVES IMPERVIOUS BOOTS AND CLOTHING TO PROTECT  
THE SKIN FROM CONTACT WITH WET CEMENT.

WORK/HYGIENIC PRACTICES  
GOOD HOUSEKEEPING PROCEDURES SHOULD BE FOLLOWED AT ALL TIMES.

=====  
SECTION IX - DISCLAIMER  
=====

DISCLAIMER  
THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT  
WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE

ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT,  
APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.