

PRE-MIXED FLEXALL® FLEXIBLE ALL-PURPOSE FILLER

- For repairing cracks in plaster, stucco, wood, concrete and tile
- Dries flexible to prevent cracks from reappearing
- Requires no mixing
- Use indoors or out

PRODUCT DESCRIPTION

Flexall® Flexible All-Purpose Filler is a pre-mixed, bridging and patching compound which dries flexible. It is a heat and water resistant material which expands and contracts with surface movement to prevent cracks from reappearing.

USES

- Flexall is used for surface repairs which require thin, bridging applications.
- Flexall will adhere to wood, metal, glass, stucco and masonry.
- It may be used for interior or exterior placement to stop water leaks to roofs, skylights, rain gutters and to cover minor cracks in stucco surfaces and wood fascia board.

LIMITATIONS

- Not for re-surfacing.
- Do not apply over a large surface area.

SURFACE PREPARATION

Surface must be clean and firm. Remove dirt, grease and loose material. Metal and glass surfaces must be dry.

APPLICATION

No mixing required. When bridging wide, open cracks in stucco and wood, reinforce Flexall with fiberglass tape. Deep fills over 1/8" (3 mm) in stucco surfaces should first be rough filled with Custom's Stucco Patch, allowed to dry, then bridged over with a coat of Flexall. Flexall may be painted over with latex coatings. Allow to dry thoroughly if coatings are used. Do not thin. Do not apply when ambient temperature is below 50° F (10° C).

DRYING TIME

3 hours depending on ambient conditions.

CLEAN-UP

Clean tools immediately with water. Use lacquer thinner if allowed to dry.

STORAGE

Close container after each use. Keep from freezing.

CAUTION

Keep out of reach of children. Do not take internally.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
DPFLXQT	1 quart (.946 L)	Off White	Tub
DPFLX1	1 gallon (3.78 L)	Off White	Pail

TECHNICAL DATA

FLEXALL	
Flammability	Non-flammable



CUSTOM®
BUILDING PRODUCTS