

CONCRETE FIX-IT-ALL™ PATCHING COMPOUND

- For patching tough, weather-resistant repairs to concrete, brick and stone
- Ideal for floors, masonry, steps, patios and sidewalks
- Vinyl reinforced
- Offers excellent adhesion and durability

PRODUCT DESCRIPTION

Concrete Fix-It-All™ is a high-strength patching compound for repairing concrete and masonry surfaces. This product is fortified with a latex polymer to increase adhesion and durability.

USES

- Concrete Fix-It-All is ideal for repairing fine cracks and large breaks in concrete walks, steps and driveways.
- It also replaces and renews deteriorated mortar joints in brick and concrete block masonry.

LIMITATIONS

- Do not apply when ambient temperatures or substrate temperatures are less than 50° F (10° C).
- Single applications must be less than 1/4" (6 mm) per application.
- Patching material only; not a surfacing agent.

SURFACE PREPARATION

Surface must be firm, clean and free of oil, grease, paints, sealer and curing compounds. An abraded surface will enhance bonding. Dampen area to be patched with clean water prior to application. Do not leave standing water.

MIXING

Combine desired volume of Concrete Fix-It-All with cool, clean water in a clean container and mix to a smooth consistency. A mixture of 1 lb. (.45 kg) to 2 1/2 - 3 oz. (74 - 89 ml) water is recommended. Do not mix more material than may be used within 1/2 hour.

APPLICATION

Apply Concrete Fix-It-All to patch area. Pack cracks and holes to eliminate air pockets and fill all voids. Use concrete trowel to finish patch flush with surrounding surface. When using Concrete Fix-It-All to replace masonry joints, scratch out all crumbling mortar before filling joints. Apply pressure to pointing trowel so as to thoroughly pack joint with new mortar.

DRYING TIME

2 hours.

CURING

24 hours.

CLEAN-UP

Clean tools with water before Concrete Fix-It-All hardens.

STORAGE

Close container after each use. Keep away from moisture.

CAUTION

Contains Portland cement. Alkaline on contact with water. Wear rubber gloves and eye protection. Avoid contact with eyes. If this occurs, flush with water repeatedly and call a physician immediately. Avoid prolonged contact with skin. Wash thoroughly after handling. Do not inhale dust. Keep out of reach of children. Do not take internally.

Warning: This product contains one or more chemicals known to the State of California to cause cancer.

Warning: Do Not Breathe Dust! This product contains free silica which may cause cancer or delayed lung injury (silicosis). Wear approved respirator in dusty areas. See Material Safety Data Sheet for detailed information.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
DPCFL6-4	6.5 lb. (2.95 kg)	Gray	Box
DPCFL25	25 lb. (11.34 kg)	Gray	Bag



CUSTOM[®]
BUILDING PRODUCTS