

# LEVELQUIK™

## LATEX PRIMER

- Prepares surfaces for self-leveling underlayments
- Improves adhesion
- Seals porous surfaces

### PRODUCT DESCRIPTION

Latex primer/sealer that prepares surfaces for the application of LevelQuik® Self-Leveling Underlayments. It seals porous surfaces and improves the bond of underlayments.

### LIMITATIONS

Do not apply to frozen surfaces or when temperatures drop below 50° F (10° C).

### SURFACE PREPARATION

All surfaces must be structurally sound, clean, dry, and free from contaminants that would prevent a good bond. All surfaces to be covered should accept water penetration. Smooth concrete, existing glazed tile, terrazzo, or polished stone flooring should be roughened or scarified. Old cutback adhesive must be properly prepared. See instructions on LevelQuik Self-Leveling Underlayment packages or data sheets.

### DILUTION

**Over smooth concrete, glazed tile, terrazzo, marble, polished stone, sheet vinyl flooring or old cutback adhesive – use undiluted.**

**Over porous concrete or plywood – dilute 1 part primer with 1 part water.**

### APPLICATION

Apply with a paint brush, short nap roller or a soft push broom. Apply a thin, even coat and allow to dry to a clear film before applying LevelQuik Self-Leveling Underlayments.

### DRYING TIME

2 hours.

### CLEAN-UP

Clean tools with soap and water.

### COVERAGE

1 quart (.946 L) bottle: 75 - 150 sq. ft. (7 - 14 m<sup>2</sup>)

1 gallon (3.78 L) bottle: 300 - 500 sq. ft. (27.9 - 46.4 m<sup>2</sup>)

### PHYSICAL PROPERTIES

**Packaging:** Quart (.946 L) and gallon (3.78 L) bottles

**Storage:** Store in a cool dry area. Keep from freezing.

### ITEM CODE

CPQT, CP1

### SAFETY

Contains acrylic emulsion. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes and consult a physician. If skin contact occurs, wash immediately with soap and water. Dried material is extremely difficult to remove.

KEEP OUT OF REACH OF CHILDREN.

DO NOT TAKE INTERNALLY.



**CUSTOM®**  
BUILDING PRODUCTS