

PRE-MIXED TILE GROUT NON-SANDED WHITE

- **Quick, easy grout repair for narrow grout joints**

PRODUCT DESCRIPTION

Pre-Mixed Tile Grout is a non-sanded white grout used to repair grout joints up to 1/8" (3 mm).

USES

For repairing narrow grout joints up to 1/8" (3 mm).

LIMITATIONS

For dry areas only. For wet areas, use White Dry Tile Grout or Polyblend® Non-Sanded Grout.

SURFACE PREPARATION

Remove a minimum of 1/16" (1.6 mm) of existing grout. Remove loose particles, clean and allow to dry.

APPLICATION

Stir grout thoroughly. Force grout into joints with a rubber grout float. Work diagonally to joints. Allow 15 minutes for grout to set-up firm in joints. Wet a clean sponge and wring out completely. Remove excess grout from tiles. Polish with a clean, dry cloth when grout hardens, about one hour. Do not expose to water for 48 hours. A longer curing time is required in cooler temperatures and in high humidity.

CLEANUP

Clean tools and hands with water before grout dries.

CARE AND MAINTENANCE

Care and Maintenance: Mold and mildew can grow on dirt, food and soap scum that can accumulate on the grout surface. Sealing the grout and keeping it clean with TileLab® products will greatly inhibit mold and mildew growth

COVERAGE

One quart fills approximately 24 sq. ft. (2.23 m²) of 4 1/4" x 4 1/4" x 1/4" (106 x 106 x 6 mm) tile with 1/8" (3 mm) grout joints.

STORAGE

Keep from freezing.

SAFETY

Keep out of reach of children.

ORDERING INFORMATION

	ITEM CODE	SIZE	COLOR	PACKAGE
USA	PMTHTPT	1/2 pint (237 ml)	White	Tub
USA	PMTQT	1 quart (946 ml)	White	Tub
Canada	CPMTQT	1 quart (946 ml)	White	Tub



CUSTOM[®]
BUILDING PRODUCTS