

WATER PUTTY ALL PURPOSE PATCHING COMPOUND

- Patches cracks, knots, nails or screw holes
- Dries hard
- Sticks, stays put
- Will not shrink

PRODUCT DESCRIPTION

Fast-setting, non-shrinking, interior/exterior patching compound used to repair cracks, knots, nail or screw holes. Dries hard to an ivory color in about one hour.

USES

- For use on plaster, wallboard, wood, cement and stone.
- For interior or exterior use.

LIMITATIONS

- If exposed to weathering, Putty must be painted. Putty will absorb moisture if exposed. Putty must be thoroughly dry before painting.

SURFACE PREPARATION

Surface must be clean, dry and firm. Concrete surfaces should be dampened with clean water. Do not leave standing water. Wood surfaces must be dry. Surface to be patched should accept water penetration in order to form a good mechanical bond.

MIXING: Combine desired 3 parts of Custom Water Putty with one part water. Stir slowly until mixture reaches a smooth consistency of heavy paste. Avoid mixing more material than can be used within 15 minutes. Once it begins to harden, discard. Do not remix.

APPLICATION

Press into cavity to be filled, smoothing off excess with a putty knife. Sets within 60 minutes depending upon temperature, humidity, and depth of application.

DRYING TIME

1 hour.

CLEANUP

Clean tools and hands with warm soapy water before material dries.

STORAGE

Store in a cool dry area.

SAFETY

Keep out of reach of children. Do not take internally. Wear rubber gloves and eye protection. Avoid prolonged contact with skin. This product may develop sufficient heat to cause burns if a large mass is allowed to harden in contact with skin.

ORDERING INFORMATION

ITEM CODE	SIZE	PACKAGE
WP1	1 lb. (.454 kg)	Can
WP4	4 lbs. (1.8 kg)	Can



CUSTOM[®]
BUILDING PRODUCTS