

QUIK-FIX® ALL PURPOSE PATCHING COMPOUND

- Repairs cracks and holes in wood, drywall and concrete surfaces
- Can be drilled, stained and painted
- Ideal as floor leveler
- Fast setting and non-shrinking
- Adheres to wood, concrete and drywall

PRODUCT DESCRIPTION

Quik-Fix® All-Purpose Patching Compound is a fast-setting, non-shrinking, interior patching compound used to repair cracks and holes in plaster, wallboard and wood surfaces. Fiber reinforcement allows Quik-Fix to be drilled, filed or nailed.

USES

- Quik-Fix is widely used for molds, models and wood repair.
- This material is formulated for interior placement where moisture is not a consideration.
- Use Patching & Leveling Latex Additive in place of water to improve adhesion, when used as a leveling compound and when adhesives will be used over Quik-Fix.

LIMITATIONS

- Quik-Fix is not recommended for exterior use or interior areas that will be exposed to continuous moisture unless it is shielded from moisture and coated with a weatherproof coating.

SURFACE PREPARATION

Surface must be clean, dry and firm. Remove dust, dirt, loose material, grease and oil. Concrete surfaces should be dampened with clean water prior to application. Do not leave standing water. Wood surfaces must be dry.

NOTE: Surface to be patched should accept water penetration in order to form a good bond. To determine if foreign substances exist in/on the surface, sprinkle water on various areas of the substrate. If water penetrates, then a good bond can be achieved. If water beads, surface contaminants are present and loss of adhesion may occur. The contaminants should be removed prior to patching. Contact Custom Building Products for recommendations on removal of foreign substances.

MIXING

Combine desired volume of Quik-Fix All-Purpose Patching Compound with cool, clean water in a clean container. Stir slowly until mixture reaches a smooth consistency of heavy paste. A mixture of 8 oz. (237 ml) of water to 1 lb. (.45 kg) Quik-Fix is recommended. Do not over-thin as this will delay set time and result in loss of strength. Avoid mixing more material than can be used within 15 minutes. Once Quik-Fix begins to harden, discard. Do not remix.

APPLICATION

When applying Quik-Fix as an underlayment, use adequate pressure against trowel to ensure that Quik-Fix fills all voids and bonds securely to surface. For patching, use broad knife or putty knife to pack void and finish flush with surface.

DRYING TIME

Quik-Fix sets within 30 minutes – depending upon temperature, humidity and depth of application.

COVERAGE

1 lb. (.45 kg) will cover approximately 1.2 sq. ft. (.11 m²) at 1/8" (3 mm) thickness.

CLEAN-UP

Clean tools with water before Quik-Fix hardens.

STORAGE

Store in cool, dry area.

CAUTION

Wear rubber gloves and eye protection. Avoid prolonged contact with skin. This product may develop sufficient heat to cause burns if a large mass is allowed to harden in contact with skin. Keep out of reach of children. Do not take internally.

Warning: This product contains one or more chemicals known to the State of California to cause cancer.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
QFX4-4	4.5 lb. (2.04 kg)	Off White	Box
QFX25	25 lb. (11.34 kg)	Off White	Bag

TECHNICAL DATA

Contains No Asbestos.

PATCHING PLASTER	
Compressive Strength	2000+ psi (140 kg/cm ²)



CUSTOM
BUILDING PRODUCTS