

CONCRETE PATCH

- Repairs minor cracks and breaks easily
- Repairs masonry mortar joints
- Durable and easy to use

PRODUCT DESCRIPTION

Concrete Patch is a high strength patching compound for repairing concrete and masonry surfaces. This product is fortified with a vinyl polymer to increase adhesion and durability.

USES

- Concrete patch repairs fine cracks and large breaks in concrete walks, steps and driveways.
- It also replaces and renews deteriorated mortar joints in brick and concrete block masonry.

SURFACE PREPARATION

Surface must be firm and clean. Remove dirt, grime and loose material. Dampen area to be patched with clean water prior to application. Do not leave standing water.

MIXING

Combine desired volume of Concrete Patch with cool, clean water in a clean container and mix to a smooth consistency. A mixture of 1 lb. (.45 kg) powder to 4 oz. (118 ml) water is recommended. Do not mix more material than may be used within 2 hours.

APPLICATION

Apply Concrete Patch to patch area. Pack cracks and holes to eliminate air pockets and fill all voids. Use concrete trowel to finish patch flush with surrounding surface. Patch will achieve initial set within 2 hours and set hard within 12 hours. When using Concrete Patch to replace masonry mortar joints, scratch out all crumbling mortar before filling joints. Apply pressure to pointing trowel so as to thoroughly pack joint with new mortar.

DRYING TIME

2 hours.

CURING

Overnight.

CLEAN-UP

Clean tools with water before Concrete Patch hardens.

STORAGE

Store in cool, dry area.

CAUTION

Contains portland cement. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately. Keep out of reach of children. Do not take internally.

Warning: This product contains one or more chemicals known to the State of California to cause cancer

Warning: Do Not Breathe Dust! This product contains Free Silica which may cause cancer or delayed lung injury (Silicosis). Wear approved respirator in dusty areas. See Material Safety Data Sheet for detailed information.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
CCP6	6.5 lb. (2.95 kg)	Gray	Box
CCP25	25 lb. (11.34 kg)	Gray	Bag



CUSTOM[®]
BUILDING PRODUCTS