

ELASTOMERIC CUSTOM PATCH® SMOOTH AND TEXTURED

- Repairs cracks in wood, drywall, plaster, concrete and masonry
- Elastomeric – Permanently flexible to prevent recurring cracks
- Water resistant – Paintable
- Seals joints on roofs, windows, skylights
- Use indoors or outdoors

DESCRIPTION

Custom-Patch® Elastomeric Patching Compound is a ready-to-use patching, sealing and bridging compound. This compound expands and contracts with surface movement to prevent cracks from reappearing. Adheres to most surfaces. Can be used indoors or out. It's available in both smooth and textured.

USES

- Use to repair cracks and holes in wood, masonry, drywall, plaster and concrete.
- Seals joints between dissimilar surfaces such as roofs, windows and skylights.
- Textured Custom-Patch is great for patching stucco surfaces.
- For interior or exterior use.

SURFACE PREPARATION

Surface must be clean, dry and firm. Remove grease and oil with a solution of Custom T.S.P. according to label directions. For cracks larger than hairline in stucco, concrete and masonry, enlarge and undercut the crack to anchor the patch. Undercut by making the crack or hole wider at the bottom than it is at the top. Dampen the surface with water. Metal and glass surfaces must be dry.

APPLICATION

Use putty knife to force material into crack. Finish flush with the surface and smooth. For cracks wider than 1/8" (3 mm) in stucco or wood, embed fiberglass tape over a thin layer of Custom-Patch. Finish with a smooth coat. For fills over 1/8" (3 mm) deep in stucco or concrete, rough fill with Custom Stucco Patch or Concrete Patch, allow to dry, then bridge over with a smooth coat of Custom-Patch. This product is not meant to be sanded. Smooth surface to desired finish while still workable. Allow to dry for 24 hours before painting or priming. Do not apply at temperatures below 50° F (10° C).

CLEAN-UP

Clean tools with water immediately. If allowed to dry, use lacquer thinner.

STORAGE

Keep from freezing. Close container after each use.

CAUTION

Keep out of reach of children. Do not take internally. If swallowed, contact physician immediately.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
CPSQT	1 quart (.946 L)	Smooth – White	Tub
CPS1	1 gallon (3.78 L)	Smooth – White	Pail
CPTQT	1 quart (.946 L)	Textured – Beige	Tub
CPT1	1 gallon (3.78 L)	Textured – Beige	Pail

TECHNICAL DATA

CUSTOM-PATCH	
Flammability	Non-flammable



CUSTOM
BUILDING PRODUCTS