

# FIX-IT-ALL™ PATCHING COMPOUND

- **Fast-setting patching compound**
- **For repairing cracks and holes in plaster, wallboard, wood, brick and concrete**
- **Strong bond**
- **Does not shrink**
- **Can be sawed and drilled when hard**

## PRODUCT DESCRIPTION

Custom's Fix-It-All™ All-Purpose Patching Compound is a fast-setting, non-shrinking patching compound in a powdered form. It mixes quickly in water and sets hard in 30 minutes. Fiber reinforcement allows Fix-It-All to be sawed, drilled, filed or sanded after drying.

## USES

- Fix-It-All is used to repair cracks and holes in plaster, gypsum, wallboard or wood surfaces.
- It has high compressive strength and therefore makes an excellent floor underlayment for patching and leveling prior to installation of resilient floor coverings.
- In addition, it can be used for models and in molds.

## LIMITATIONS

- Fix-It-All is not recommended for exterior use or interior areas that will be exposed to continuous moisture, unless it is shielded from moisture and coated with a weatherproof coating.
- Apply only when ambient temperatures are 50° - 80° F (10° - 27° C).

## SURFACE PREPARATION

Surfaces must be clean and sound. Remove all oil, grease, paint, sealers, curing compounds, dust and foreign or loose materials. A solution of T.S.P. will cut dirt and grease from most surfaces. Sponge-dampen concrete surfaces prior to application. Wood surfaces must be dry. Fix-It-All is formulated for interior use in dry areas. Avoid areas continuously exposed to water. Do not place on concrete where a hydrostatic moisture condition may exist.

## MIXING

Combine the desired volume of Fix-It-All with cool, clean water and mix to a heavy paste consistency. Always use clean tools and mixing containers. A mixture of 6 1/2 oz. (192 ml) water to 1 lb. (.45 kg) powder is recommended. Do not overthin. Avoid mixing more than can be used within 10 minutes.

## DRYING TIME

30 minutes.

## CLEAN-UP

Clean tools with water before Fix-It-All hardens.

## STORAGE

Close container after each use. Store in a cool, dry area. Keep from freezing.

## CAUTION

It is recommended that an approved respirator be worn while sanding. Wear rubber gloves and eye protection. Avoid prolonged contact with skin. This product may develop sufficient heat to cause burns if a large mass is allowed to harden in contact with the skin. Keep out of reach of children. Do not take internally.

## ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
DPFXL1	1 lb. (.45 kg)	Off White	Box
DPFXL4-4	4.5 lb. (2.04 kg)	Off White	Box
DPFXL25	25 lb. (11.34 kg)	Off White	Bag

## TECHNICAL DATA

FIX-IT-ALL	
Compressive Strength	1000+ psi (70.3 kg/cm <sup>2</sup> )



**CUSTOM**<sup>®</sup>  
BUILDING PRODUCTS