

# PATCH-N-PAINT® WALL REPAIR PATCH KIT

- **Quick-drying, easy-to-use**
- **Strong, flexible, resilient, durable plastic**
- **Won't rust or dent like metal reinforced patches**
- **Nonwoven fabric easily blends into surrounding surfaces**

## PRODUCT DESCRIPTION

Patch-N-Paint® Wall Repair Patch Kit includes everything you need to make quick, easy repairs to holes in walls, ceilings, paneling, doors and more. The kit contains Patch-N-Paint® Lightweight Spackling, 6" (15 cm) diameter fiber patch, sandpaper and putty knife.

## APPLICATION

**Step 1.** The 6" (15 cm) round, fiber patch will cover up to a 4" (10 cm) hole in drywall, plaster, paneling, hollow-core doors, etc. Check the size of the hole to be repaired to ensure the patch will properly cover it. Make certain the area surrounding the area to be patched is clean and free of dirt, dust, oil, or anything which might impair adhesion. Remove any loose paint or plaster.

**Step 2.** Peel the paper backing from the self-adhesive, fiber patch. Position the patch over the damaged section. It is important that the 4" (10 cm) center of the patch completely covers the area to be patched, allowing the outer 2" (5 cm) circle of the patch to adhere to the solid surrounding area. Press firmly around the outer edge of the patch to ensure thorough adhesion.

**Step 3.** Using the putty knife, apply a thin coat of Custom® Patch-N-Paint® Lightweight Spackling to the patch and the surrounding area, and allow to dry. Refer to the back panel of the Patch-N-Paint container for complete directions for proper application and clean-up. Allow the Patch-N-Paint to dry thoroughly before the next step.

**Step 4.** Use the sandpaper to sand the thin coat of Patch-N-Paint to a smooth finish. If the damage to the area is extensive, you may want to repeat steps 3 & 4. After your final sanding, the repair is complete. You may now texture, paint or hang wallpaper over the area.

## CLEAN-UP

Clean tools and hands with water before material dries.

## STORAGE

Close container after each use. Keep from freezing.

## CAUTION

Do not take internally. May irritate eyes. Avoid eye contact. Avoid prolonged inhalation of dust should sanding be necessary. If eye contact occurs, flush immediately with plenty of water for 15 minutes. Contact physician immediately. Keep out of reach of children. Do not take internally.

## ORDERING INFORMATION

ITEM CODE	SIZE
WRPK-12	Kit contains: 1/2 pint (237 ml) Patch-N-Paint Lightweight Spackling, 6" (15 cm) diameter fiber patch, sandpaper and putty knife



**CUSTOM®**  
BUILDING PRODUCTS