

PATCH-N-PAINT® LIGHTWEIGHT SPACKLING

- Interior/Exterior
- Repairs cracks and holes in one application
- Shrink resistant — Non-sag
- Quick drying
- No sanding
- Ready-to-use

PRODUCT DESCRIPTION

This easy to use, ready-mixed spackle fills cracks, holes and dents in one application. Resists shrinking, cracking and sagging. Ready to paint in minutes. No sanding required.

USES

- Use on plaster, drywall, masonry and wood.
- For interior or exterior use.

LIMITATIONS

- Not recommended for use on floors.
- Must be painted over when used on exterior surfaces.
- Do not apply at temperatures below 50° F (10° C).

SURFACE PREPARATION

Surface must be clean, dry and firm. Lightly sand to ensure adhesion. Bare wood should be primed prior to application with latex primer. A solution of T.S.P. or T.S.P. Substitute can be used to clean grease and dirt to achieve a better bond.

APPLICATION

Stir thoroughly. Use putty knife to force material into patch. Finish flush with the surface and smooth. May be painted or primed in 15-20 minutes. For best results, priming is recommended when using oil-based paint or gloss latex paint. Must be painted over when used on exterior surfaces. If material appears too dry after opening, add one teaspoon (4.9 ml) of water to each 8 oz. (236.5 ml) of material and mix.

DRYING TIME

15 - 20 minutes.

CLEANUP

Clean tools and hands with warm soapy water before material dries.

STORAGE

Keep from freezing. Close container after each use.

SAFETY

Keep out of reach of children. Do not take internally. May irritate eyes. Avoid eye contact. Avoid prolonged inhalation of dust should sanding be necessary. If eye contact occurs, flush immediately with plenty of water for 15 minutes. Contact physician immediately.

ORDERING INFORMATION

ITEM CODE	SIZE	PACKAGE
PNPHPT	1/2 pint (237 ml)	Tub
PNPQT	1 quart (.946 L)	Tub
PNP1-2	1 gallon (3.78 L)	Pail



CUSTOM®
BUILDING PRODUCTS