

# PATCHING PLASTER

- For interior plaster repairs
- May be drilled, sanded and painted
- Can be textured to match existing surfaces

## PRODUCT DESCRIPTION

Custom's Patching Plaster is a gypsum-based plaster repair compound that dries in 90 minutes.

## USES

- Patching Plaster is used to repair surface cracks or holes on interior plaster walls or ceilings.
- It dries hard to a uniform white color and may be painted.
- Patching Plaster will absorb paint similar to the surrounding plaster areas to aid in giving uniform appearance to the patch area.
- It can be textured to match existing surface.

## LIMITATIONS

- Not intended for exterior use.

## SURFACE PREPARATION

Surface must be clean, dry and firm. Remove dust, paint, foreign and loose materials. A solution of Custom's T.S.P. will cut dirt and grease from most surfaces. Open cracks to lock in patch by undercutting edges to an inverted "V". Sponge dampen patch area with water prior to application.

## MIXING

Combine desired volume of Patching Plaster with cool, clean water in a clean container and mix to a heavy paste consistency. A mixture of 6 oz. (177 ml) water to 1 lb. (.45 kg) powder is recommended. Do not overthin. Avoid mixing more material than can be used within 60 minutes. The use of Concrete and Plaster Adhesive (C.P.A.) as a mixing agent may be advisable to promote a better bond in problem areas such as ceilings and outside corners.

## APPLICATION

Using medium pressure against tool, pack Patching Plaster into void and finish flush with surface. Fills over 1/4" (6 mm) require two applications. Allow patch to set for 90 minutes. Complete by troweling on additional material level with surface. Match surrounding texture. Sand, if necessary. Allow repair to dry thoroughly. Prime before painting or wallpapering.

## DRYING TIME

30 minutes.

## CURING

2 1/2 hours.

## CLEAN-UP

Clean tools with water before Patching Plaster hardens.

## STORAGE

Keep from freezing. Store in a cool, dry area.

## CAUTION

Wear rubber gloves and eye protection. Avoid prolonged contact with skin. This product may develop sufficient heat to cause burns if a large mass is allowed to harden in contact with the skin. Keep out of reach of children. Do not take internally.

## ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
PPL4-4	4.5 lb. (2.04 kg)	White	Box
PPL25	25 lb. (11.34 kg)	White	Bag



**CUSTOM**<sup>®</sup>  
BUILDING PRODUCTS