

PRE-MIXED CONCRETE PATCH

- For repairing cracks and breaks in concrete and mortar joints
- Ready to use
- For interior and exterior repairs

PRODUCT DESCRIPTION

Custom's Pre-Mixed Concrete Patch is a high strength patching compound for repairing concrete and masonry surfaces. This product is fortified with a vinyl polymer to increase adhesion and durability.

USES

- Pre-Mixed Concrete Patch fills holes and repairs cracks, chips and other imperfections in concrete.
- It can also be used to bond broken pieces of concrete and to repair deteriorated mortar joints.

LIMITATIONS

- Pre-Mixed Concrete Patch is not recommended for surfaces subject to vehicle traffic.
- Do not patch areas with Pre-Mixed Concrete Patch that are subject to prolonged water exposure or under complete water submersion.

SURFACE PREPARATION

Surface must be clean and free of loose particles, dirt, dust and grease. Use a wire brush or other tool to clean the area to be patched. Rough up the surface an inch or two beyond the patch area to improve bonding. Dampen the patch area with clean water, but do not leave standing water. Surface to be patched should accept water penetration. To check absorption rate, sprinkle water on various areas of the substrate. If water beads, loss of adhesion may occur.

MIXING

Mix contents prior to application.

APPLICATION

Stir contents thoroughly. For repairing cracks and holes use a putty knife or similar tool to apply compound to patch area. Compound may be smoothed or featheredged. Fills greater than 1/4" (6 mm) deep require two or more applications. For repairing broken pieces of concrete apply compound as if it were a glue and push broken piece tightly into place. Excess Pre-Mixed Concrete Patch should be removed with a cloth, putty knife or other tool. Allow overnight drying for surface patching and longer for deep fills. For use in repairing mortar joints in brick and concrete block masonry, Pre-Mixed Concrete Patch should be pressed firmly with pointing trowel to pack joint with new mortar. Do not apply at temperatures below 50° F (10° C).

CLEAN-UP

Clean tools with warm, soapy water before material dries.

STORAGE

Keep from freezing. Close container after each use.

CAUTION

Avoid eye contact. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately. Keep out of reach of children. Do not take internally.

ORDERING INFORMATION

| ITEM CODE | SIZE | PACKAGE |
|-----------|-------------------|---------|
| PMCQT | 1 quart (.946 L) | Tub |
| PMC1 | 1 gallon (3.78 L) | Pail |



CUSTOM[®]
BUILDING PRODUCTS