

PRE-MIXED STUCCO PATCH

- For repairing minor cracks in stucco
- Ready to use
- Durable and flexible
- Can be textured to match surrounding stucco

PRODUCT DESCRIPTION

Custom's Pre-Mixed Stucco Patch is an easy to use patching compound for stucco repair. It creates a hard durable patch which when painted blends evenly with the original stucco. Pre-Mixed Stucco Patch is mildew and weather resistant.

USES

- Pre-Mixed Stucco Patch is used to repair cracks, holes and breaks up to 1/4" (6 mm) thickness in exterior and interior stucco surfaces.
- This product is formulated so that the applicator can match the texture of the surrounding stucco.

SURFACE PREPARATION

Surface to be patched must be clean, firm and dry. Remove all loose particles, scaling paint and dirt.

APPLICATION

No mixing required. Use broad knife or putty knife to apply Stucco Patch to surface. A rubber stucco float is recommended for spreading and texturing Stucco Patch to blend with existing surfaces. Thin cracks and small surface breaks may be repaired with one application. Deeper cracks and holes over 1/4" (6 mm) require two applications. Apply the first application to just below surface and allow to dry. Apply second coat and blend to match surrounding texture. Average drying time is one hour depending upon temperature, humidity and depth of patch. Follow paint manufacturers instructions to prime patch area prior to applying paint. Do not apply if air temperature is below 50° F (10° C).

DRYING TIME

1 hour ±.

CLEAN-UP

Clean tools with warm soapy water before Stucco Patch hardens.

STORAGE

Keep from freezing. Close container after each use.

SAFETY

Contains Petroleum Distillates. If ingested, do not induce vomiting. Call a physician immediately. Use adequate ventilation. Non-flammable. Keep out of reach of children. Do not take internally.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
PMSQT	1 quart (.946 L)	Off White	Tub
PMS1-2	1 gallon (3.78 L)	Off White	Pail



CUSTOM[®]
BUILDING PRODUCTS