

STUCCO PATCH

- Repairs large cracks and holes in stucco
- Can be textured to simulate surrounding stucco
- Produces a hard, durable patch

PRODUCT DESCRIPTION

Custom's Stucco Patch is a powdered patching compound for stucco repair that creates a hard durable patch which may be textured to blend evenly with the original stucco. Stucco Patch contains adhesive compounds which create high bond strengths.

USES

- Stucco Patch is used to repair cracks, holes and breaks in exterior and interior stucco surfaces.
- This product is formulated to match the texture and porosity of existing stucco surface.

SURFACE PREPARATION

Surface must be firm and clean. Remove dirt, grime and loose material. Open cracks to lock in patch by undercutting edges to an inverted "V". Dampen area to be patched with clean water prior to application.

MIXING

Combine desired volume of Stucco Patch with cool, clean water in a clean container and mix to a smooth, stiff consistency. A mixture of 3 oz. (89 ml) water to 1 lb. (.45 kg) powder is recommended. Do not overthin. Avoid mixing more material than may be used within 2 hours.

APPLICATION

Apply Stucco Patch to dampened surface with proper tool and finish flush with surface. Match surrounding stucco texture with sponge, brush, trowel, or stucco float to blend repair into original stucco. Corner repairs should bridge both surfaces to insure a stable patch. Allow to cure 24 hours before priming and painting. On applications where temperatures exceed 80° F (27° C), lightly mist patched area periodically with clean, cool water.

DRYING TIME

3 hours.

CURING

28 days.

CLEAN-UP

Clean tools with water before Stucco Patch hardens.

STORAGE

Store in a cool, dry area.

CAUTION

Contains Portland cement. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately. Keep out of reach of children. Do not take internally.

Warning: This product contains one or more chemicals known to the State of California to cause cancer.

Warning: Do Not Breathe Dust! This product contains Free Silica which may cause cancer or delayed lung injury (Silicosis). Wear approved respirator in dusty areas. See Material Safety Data Sheet for detailed information.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
STP6	6.5 lb. (2.95 kg)	White	Box
STP25	25 lb. (11.34 kg)	White	Bag



CUSTOM[®]
BUILDING PRODUCTS