

TILE REPAIR MORTAR

- Replace broken tile
- Easy to use
- Polymer-modified – Just add water

PRODUCT DESCRIPTION

Tile Repair Mortar can be used to replace any type of tile. Polymer-modified for maximum bond strength. Dries hard and is ready for grouting in 24 hours.

USES — TILE TYPES

For replacing:

- Ceramic, mosaic, quarry or porcelain tile
- Brick and mini-brick
- Precast terrazzo
- Natural stone tile

AREAS OF USE

- Interior or exterior floors, countertops, walls
- Concrete, mortar beds, masonry, Portland cement plaster
- WonderBoard®, RhinoBoard™ cement backerboards
- Exterior grade plywood
- Gypsum wall board
- Water-resistant wallboard
- Existing ceramic tile
- Sheet vinyl flooring, VCT
- Plastic laminates
- Cutback adhesive

LIMITATIONS

- Do not bond directly to hardwood, Luan plywood, particle board, parquet, cushion or sponge-back vinyl flooring, metal, fiberglass, plastic and OSB panels.
- When setting moisture sensitive stone, tile or agglomerates (check with manufacturer) use OptiCure™ Fortified Thin-Set Mortar or 100% Solids Epoxy Mortar.
- Do not use to install resin-backed stone.

SURFACE PREPARATION

Remove cracked or broken tile. Scrape or chisel out old thin-set or mastic so that new tile will sit flush with the surrounding tile. Make sure surface is dry and free from dust or other contaminants which may inhibit bond.

MIXING

Approximately 3 oz. (89 ml) of clean, cool water per pound of Tile Repair Mortar.

APPLICATION

Use proper sized notch trowel to ensure 100% coverage under tiles. Using flat side of trowel, apply skim coat of mortar to the surface. Apply additional mortar with notched side of trowel held at a 45° angle to the surface, combing in one direction. Press tile firmly into place in a perpendicular motion across ridges, moving back and forth. Perpendicular pressing flattens ridges and closes valleys allowing maximum coverage. When replacing tiles where Tile Repair Mortar cannot be applied with a notch trowel, apply a sufficient amount of mortar to back of tile (back butter) to ensure 100% coverage of mortar to tile and the proper amount of mortar under the tile after placement. Periodically pull up a tile and check the back to ensure complete coverage with the adhesive. If material has skinned over (not sticky), recomb with notched trowel. If too dry, remove and replace with fresh material.

COVERAGE

Approximately 1 1/2 - 2 sq. ft. per pound (.31 - .41 m² per kg).

CLEAN-UP

Clean tools with water before material hardens.

STORAGE

Store in cool, dry area.

SAFETY

Contains Portland cement. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately. Keep out of reach of children. Do not take internally.

ORDERING INFORMATION

	ITEM CODE	SIZE	COLOR	PACKAGE
USA	TRM1	1 lb. (.45 kg)	White	Box
Canada	CTRM1	1 lb. (.45 kg)	White	Box



CUSTOM
BUILDING PRODUCTS