

WALLBOARD JOINT COMPOUND

- All-purpose for taping and finishing wallboard
- Use as a texturing medium for walls
- Sands easily

PRODUCT DESCRIPTION

Custom's All Purpose Wallboard Joint Compound is a pre-mixed, all-purpose compound for taping, finishing and texturing gypsum wallboard.

USES

- Use to cover and finish gypsum wallboard joints, cornerbead, screw or nail holes.
- It may also be used to patch and texture interior walls.

SURFACE PREPARATION

Inspect all wallboard fastening nails and drive protruding nails below surface leaving 1/32" (.8 mm) depression in surface of paper of panel.

APPLICATION

Remix before using. Spread Wallboard Joint Compound evenly along joints between panels with a broad knife. Fill all depressions and joints. Cover an area 2" - 4" (5 - 10cm) on either side of joint. Immediately embed wallboard tape while material is wet by pressing tape into wet compound with broad knife. Continue along entire joint, smooth tape and excess material. Let dry overnight. When application is dry, cover with topping coat and let dry overnight. For a superior finish, add a third application. This final topping coat should be featheredged to a width of 4" - 6" (10 - 15 cm) on both sides from the center of the joint. After this coat has dried, sand lightly. May also be used as a decorative plaster finish. Apply with a heavy paint roller or plaster trowel to a uniform 1/32" (.8 mm) thickness. A variety of texturing tools may be used. Allow application to dry thoroughly prior to painting. Do not apply to wall temperatures below 50° F (10° C).

DRYING TIME

12 - 24 hours

COVERAGE

62 lbs. (28 kg) covers approximately 370 lineal feet (112 lineal meters) of gypsum wallboard joints. 50 lbs. (22.68 kg) covers approximately 248 square feet (23 m²) as a texturing medium at 1/32" (.8 mm) thick.

CLEAN-UP

Clean tools with water after use, before compound hardens.

STORAGE

Keep from freezing. Store in a cool, dry area. Close container after each use.

CAUTION

It is recommended that an approved respirator be worn while dry sanding. Wet sanding or sponging is preferable whenever possible, to avoid dust. Wear rubber gloves and eye protection. Avoid eye contact. If contact occurs flush with water for 15 minutes. Call a physician immediately. Keep out of reach of children. Do not take internally. Non-flammable.

ORDERING INFORMATION

ITEM CODE	SIZE	COLOR	PACKAGE
WJCQT	1 quart (.946 L)	Off White	Tub
WJC12P	12 lb. (5.45 kg)	Off White	Pail
WJC62P	62 lb. (28.12 kg)	Off White	Pail

TECHNICAL DATA

WALLBOARD JOINT COMPOUND	
Flammability	Non-flammable

