

TILELAB®

HEAVY-DUTY CLEANER & STRIPPER

- For tough jobs and removing acrylic and wax floor finishes
- Safe for tile, stone, marble and grout
- Cuts through dirt, grease and heel marks
- Removes light grout haze

PRODUCT DESCRIPTION

Concentrated cleaner and stripper for tough cleaning jobs. Cleans heavy build-up of dirt, grease, scuff marks, mold and mildew stains. Strips wax and acrylic floor finishes. Great for renewing old tile installations. Will also remove light cement grout haze and mortar residue. Will not harm the surface and there are no strong fumes or odors.

USES

Use on tile, stone, grout, cement, masonry and vinyl flooring.

DIRECTIONS

Remove all loose dust and dirt from the surface. For stripping or removing wax and acrylic floor finishes, light cement grout haze or mortar residue use full strength. For normal heavy-duty cleaning: Mix 1 part Heavy-Duty Cleaner & Stripper with 7 parts water. For stronger cleaning action: Mix 1 part with 5 parts water. Liberally apply with sponge or mop and allow to stand for 3 - 5 minutes. Do not allow it to dry. Lightly scrub the surface with a nylon scrub brush or scrub machine. Remove residue with a mop or wet vacuum. Repeat as necessary. When cleaning or stripping is completed, rinse thoroughly with water and remove residue with mop or wet vacuum. Allow at least 48 hours drying time before applying a sealer or finish.

Note: When using diluted as a cleaner, Heavy-Duty Cleaner & Stripper can remove wax coatings such as TileLab® StoneGloss™ Polish and dull acrylic finishes such as TileLab Sealer & Finish. If dulling occurs, renew by applying one coat of finish according to label directions. When used full strength, it will strip acrylic finishes.

COVERAGE

For Cleaning:

One gallon (3.78 L) when diluted 7:1 will clean 800 - 2400 sq. ft. (74.3 - 223 sq. m).

One quart (946 ml) when diluted 7:1 will clean 200 - 600 sq. ft. (18.6 - 55.7 sq. m).

For Stripping:

One gallon (3.78 L) will strip 100 - 300 sq. ft. (9.3 - 27.9 sq. m).

One quart (946 ml) will strip 25 - 75 sq. ft. (2.3 - 7.0 sq. m).

CLEAN-UP

Clean tools and hands with soap and water immediately after use.

PACKAGING

1 quart (946 ml) and 1 gallon (3.78 L) bottle.

ITEM CODES

TLSTSQT, TLSTS1

VOC

600 grams of VOC per liter of material less water and exempt solvents.

CAUTION

Keep out of reach of children. Contains butyl-cellulose and high alkaline salts. Harmful if swallowed. Do not induce vomiting. Give plenty of water and call a physician immediately. Wear rubber gloves and eye protection. If eye contact occurs, flush immediately with plenty of water for 15 minutes. If contact with sensitive skin occurs, wash with soap and water. Call physician if necessary. Do not mix with other solutions. Keep from freezing.



CUSTOM®
BUILDING PRODUCTS