



GROUT

Polyblend® Sanded Grout

Polyblend® Non-Sanded Grout

Saltillo Grout Mix

100% Solids Epoxy Grout

COLORS

For Ceramic Tile and Stone



CUSTOM® BUILDING PRODUCTS

SELECT

THE PERFECT GROUT COLOR

Consider where the grout is going to be used, a darker shade tends to show less dirt.



For a uniform look, select a grout color that is a close match to the tile for a tone on tone effect. This will make the room look bigger.

Choosing a shade that is slightly different than the tile color will give your installation more depth and interest.

Installations by norberrytile.com

To emphasize each tile, choose a grout in a contrasting color. The grout then acts as a frame for each tile giving the installation a grid effect.



CUSTOM BUILDING PRODUCTS

GROUTS



Polyblend® grouts are easy to use.

Just add water and mix! Choose from 48 impressive colors to match your style.

Polyblend® Sanded Grout – For grout joints from 1/8" to 1/2" wide. Polyblend's unique formula offers color consistency, quick setting time and a smooth texture for easy spreading and clean-up. It produces dense joints that are highly resistant to shrinking, cracking, powdering and wear. Exceeds ANSI A118.6 requirements.

Polyblend® Non-Sanded Grout – For narrow joints up to 1/8" wide. Excellent for highly glazed ceramic tile and highly polished marble or natural stone that can be scratched by sanded grouts. It's non-shrinking and durable. Exceeds ANSI A118.6 requirements.

Saltillo Grout Mix – For wide joints from 1/2" to 1-1/4" often used when installing saltillo, terra-cotta or other clay pavers. Pre-mixed blend eliminates the need for site mixing.

100% Solids Epoxy Grout – For residential, commercial or industrial applications where high resistance to staining and chemical attack is desired. For grout joints 1/8" – 3/8" wide. Resin and hardener mix with any Polyblend Sanded Grout color. Meets ANSI A118.3 requirements.

COVERAGE

Tile Size	Polyblend Sanded Sq. ft. per 25 lb. bag					Polyblend Non-Sanded Sq. ft. per 10 lb. box		100% Solids Epoxy Sq. ft. per unit				Saltillo Grout Mix Sq. ft. per 50 lb. bag			
	Joint Width >	1/8"	3/16"	1/4"	3/8"	1/2"	1/16"	1/8"	1/8"	3/16"	1/4"	3/8"	3/4"	1"	1-1/4"
1" x 1" x 3/16"									80	55	50	40			
1" x 1" x 1/4"	63	40	25	23	20	44	20								
2" x 2" x 1/4"	88	73	50	40	33	85	40	110	74	60	45				
3" x 3" x 1/4"	150	103	80	55	45	126	60	155	106	82	58				
4" x 4" x 1/4"								204	139	104	72				
4" x 8" x 1/2"	115	78	56	38	25			130	91	70	48				
4-1/4" x 4-1/4" x 1/4"	210	143	110	75	60	149	78	215	147	110	80				
6" x 6" x 1/4"	263	178	136	93	70	250	120	295	204	155	106				
6" x 6" x 1/2"	130	88	63	44	31	125	60	150	102	77	54				
6" x 8" x 1/4"	298	200	153	105	80	284	140								
8" x 8" x 3/8"	230	155	113	75	50	220	110								
8" x 8" x 1/2"								195	133	100	70				
8" x 8" x 3/4"												37	30	25	
12" x 12" x 3/8"	345	230	175	118	90	331	171					55	42	35	
12" x 12" x 1/2"								290	199	150	100				
16" x 16" x 3/8"	458	305	225	144	94										
24" x 24" x 3/8"	685	458	325	225	150										

Sample colors shown approximate as nearly as possible the color of the grout. Final installed shade may vary with the tile type and porosity, job site conditions or finishing techniques. Uneven drying conditions can cause shading variations or mottling.

Custom Building Products
Seal Beach, CA 90740
Nationwide manufacturing facilities

Customer Support
800-272-8786
www.custombuildingproducts.com

Printed in the U.S.A.
©2002 Custom Building Products
CC 03/04 R

To protect against stains, we recommend sealing grout, stone and unglazed tile with TileLab® Sealers. TileLab offers a complete line of products for ongoing care and maintenance of your installation.



CARE & MAINTENANCE